

Returning Values From Functions

023 RETURNING MULTIPLE VALUES

```
def squared(x, y, z): 1 usage
    return x * x, y * y, z * z
t = squared(x:2, y:3, z:4)
print(t)
```

Returning Values From Functions

`result = 8`



This is the returned value after successful completion of `sum(5, 3)`. Thus result will now store value 8.

Returning Values From Functions

Returning Values From Functions

*void function but
no return statement*

```
def greet( ):  
    print("helloz")
```

*void function with a
return statement*

```
def quote( ) :  
    print("Goodness counts!!")  
    return
```

Another void function with no return statement

```
def greet1(name) :  
    print("hello", name)
```

```
def prinSum (a, b, c) :  
    print("Sum is", a + b + c)  
    return
```

*Another void function
with a return statement*

Returning Values From Functions

Returning Values From Functions

Code 1

```
def replicate():  
    print("$$$$$")  
  
print(replicate())
```

Code 2

```
def replicate1():  
    return "$$$$$"  
  
print(replicate1())
```

Returning Values From Functions

Returning Values From Functions

➤ **Returning Multiple Values**

Returning Values From Functions

```
def squared(x, y, z):  
    return x * x, y * y, z * z
```

The return statement returning comma separated multiple values (expressions)

```
t = squared(2, 3, 4)  
print(t)
```

Tuple t will be printed as:

(4, 9, 16)

Variable *t* that receives the returned values is a tuple (recall that comma separated values are taken as a tuple)

Now you can use the tuple *t* with usual operations

024 PROGRAM TO DO ARITHMETIC OPERATIONS

```
def arcalc(x, y): 1 usage
    return x+y, x-y, x*y, x/y, x%y
num1=int(input("Enter Number 1: "))
num2=int(input("Enter Number 2: "))
add, sub, mult, div, mod = arcalc(num1, num2)
print("Sum of given Numbers: ", add)
print("Subtraction of given Numbers: ", sub)
print("Product of given Numbers: ", mult)
print("Division of given Numbers: ", div)
print("Modulo of given Numbers: ", mod)
```

Returning Values From Functions

```
def squared(x, y, z):  
    return x * x, y * y, z * z
```

Now the received values are in the form of three different variables, not as a tuple

```
v1, v2, v3 = squared(2, 3, 4)  
print("The returned values are as under:")  
print(v1, v2, v3)
```

Output produced as::

The returned values are as under:

4 9 16

Returning Values From Functions

```
def arCalc(x, y) :  
    return x+y, x-y, x*y, x/y, x%y  
  
# __main__  
num1 = int(input("Enter number 1 : "))  
num2 = int(input("Enter number 2 : "))  
add, sub, mult, div, mod = arCalc(num1, num2)  
print("Sum of given numbers :", add)  
print("Subtraction of given numbers :", sub)  
print("Product of given numbers :", mult)  
print("Division of given numbers :", div)  
print("Modulo of given numbers :", mod)
```